



**МЕТАФРАКС
КЕМИКАЛС**

UREA

Regulatory document

GOST 2081-2010 "UREA. Technical specifications".

Application

Product is intended for use in industry as a raw material in the manufacture of resins, adhesives, etc.

Packaging

Product to be packaged in specialized containers in accordance with the rules of cargo transportation applicable to this type of transport.

Transportation and storage

Product to be transported by all modes of transport in accordance with the rules of cargo transportation, applicable to this type of transport. Product to be transported in bulk in covered specialized wagons (hoppers) by wagon shipments.

Product to be stored in covered, well-ventilated warehouses that protect the product from direct sunlight and precipitation.

Manufacturer's guaranty

Guaranty period of storage is 6 months from the date of manufacture, provided that all transportation and shipment rules are observed.

Sales of product

Metafrax Trading, LLC
Yuri Bystrykh
Ph: +7(984) 000 19 88
E-mail: manager@metafrat.ru

Sales of product for export

Pavel Pirogov
Ph: +7(984) 000 10 55
E-mail: info@metafrat.ru



ΜΕΤΑΦΡΑΚΣ ΚΕΜΙΚΑΛΙΣ

Physical and chemical parameters

Type A - for industry

Type A

Name of parameter	Norm for the Grade
	1st grade
Mass fraction of nitrogen on dry basis, %, not less	46.2
Mass fraction of biuret, %, no more	1.4
Mass fraction of free ammonia, %, not more	
For urea:	
crystal	0.01
granular	0.03
Mass fraction of water, %, no more:	
hygroscopic	0.3
total	0.6